# Agricultural Equipment and Supplies 2018

**New Products** 







# **Trailer Camera Set Digital with Monitor 7.0**"

The digital wireless camera system for trailers, transport and shed

The Trailer Camera for anyone who wants to keep an eye on everything on their 7" screen. The high-quality, wide-angle Camera supplies razor-sharp images from the trailer to the screen. A powerful package for monitoring animals in the trailer while they're being transported.

Camera • CMOS image sensor (510 x 492 pixels) • 100° angle of view • minimal exposure 2 lux / F1.2 & 0 lux (IR on) • 5 volt DC • charging time: 4 hours • up to 4 hours in standby (IR off) / up to 3 hours (IR on) • visibility up to 100 m (depending on situation) • night vision range 5 m • dimensions (W x D x H) 28 x 90 x 28 mm (without mounting) • weight 205 g • working temperature: -20°C ~ +60°C • IP65 water and dust protection

Monitor • digital LCD screen with 7.0" • resolution 800 x 480 pixels (RGB) • with rear view camera (mirror display / up-down view / distance display) • 2 channels for up to 2 cameras • 11 - 32 volt DC • dimensions (W x D x H) 185 x 50 x 123 mm • weight 380 g

| Supplied package                           |
|--|
| 2.4 GHz camera with magnetic foot (IP65)   |
| 7.0" wireless monitor 2-canal 2.4 GHz      |
| Charge cable 12 V DC for cigarette lighter |
| Car holder for monitor                     |
|  |

Fixed connection cable for camera 12 V




| ref. no. | description                                  | €    |
|----------|--|------|
| 322069   | Trailer camera set digital with 7.0" monitor | 1/5  |
| 322057   | Camera only for 322069                       | 1    |
| 322059   | Monitor 7 "digital only for 322069           | 1    |
| 322031   | LCD monitor 2.5", separate                   | 1/5  |
| 1083     | Antenna with magnetic foot, 1.5 m cable      | 1/30 |

# Refractometer

### Colostrum measuring device

• for the accurate and rapid determination of colostrum milk quality • the quality level of the colostrum can be quickly ascertained with impressive accuracy with just one look through the lens • suitable for cow and horse colostrum • accessories: Pipette, screwdriver, fabric cloth, bag • packaged in high-quality case





# Colostrometer Colostrum measuring device • for the quick and easy determination of colostrum quality • it measures the gamma globulin content via the specific density • colostrum quality can be read off from the colour scale on the spindle ref. no. 1459 1/100

### ColostroStart

### Colostrum management

The feeding of calves during the first days of life or even immediately after birth is crucial for their further development. First milk, also known as colostrum, has a higher percentage of immunoglobulins and nutrients compared to normal cow's milk. Consequently, the new-born calf needs to take in higher quantities of the high-quality colostrum straight away. It is recommended that a colostrum store be created with frozen colostrum. This means that there is always a stock of high-quality first milk available. If the quality of the colostrum after birth is poor (e.g. in heifers) or the amount produced is too low, frozen colostrum can be used instead.

### Colostrum management - ColostroStart

The products in our ColostroStart Colostrum Management System are the best way to help you to provide your new-born calves with colostrum. The aluminium pouches (4 litres) are easy to fill and can be pasteurised (optional), frozen and reheated without any problems. To administer the colostrum, simply screw on the drinking teat or drencher probe.

We have put together retail sets geared towards your needs:

### ColostroStartSET 10

• 10 colostrum bags • 1 teat • 1 drencher probe


### ColostroStartSET 50

• 50 colostrum bags • 3 teats • 3 drencher probes

To make filling the pouches even easier, we offer you the ColostroFILLER filling tool. The optional ColostroCASE drinks trough bag keeps the first milk warm for longer, making feeding easier.

Here's how it work:

TV






# **Feeding Bucket Transparent**

- fill level easy to see from a distance with printed scale on the back additional embossed scale on the inside with metal handle acid-proof
- food safe easy to clean available in various transparent colours (white, yellow, pink, blue)

**The choice is yours!** Design your own feeding bucket. All of our valves can be combined with the feeding buckets.





| ref. no. | colour             | content |      |     | € |
|----------|--------------------|---------|------|-----|---|
| 14266    | white transparent  | 8 I     | 1/10 | 240 |   |
| 14267    | yellow transparent | 8       | 1/10 | 240 |   |
| 14268    | pink transparent   | 8       | 1/10 | 240 |   |
| 14269    | blue transparent   | 8       | 1/10 | 240 |   |

| ref. no. | description                            |      | € |
|----------|--|------|---|
| 14276    | Screw Valve 149 + Super-Teat 147       | 1/50 |   |
| 14277    | Screw Valve 149 + Latex-Teat 1454      | 1/50 |   |
| 14278    | Hygienic Valve with Teat               | 1    |   |
| 14279    | FixClip Valve with Natural Rubber Teat | 1    |   |

# **Calf Feeder Tray Multi Feeder**

### No portioning

- for the simultaneous provision of drinks to up to 5 calves
- with Super Teats, latex teats or Big Softy Teats facilitates observation of the animals during milk intake no portioning and with rounded corners, making it very easy to clean for hanging on barn walls, feed barriers, fences, etc. (pipes up to max. Ø 61 mm (2") with easy to operate rotary snap closure for fixing and securing the tray ideal for Large Calf Hutch CalfHouse Premium 4/5 (ref. no. 14440) stackable easy to transport acid-proof food safe dimensions (L x W x H): 700 x 354 x 278 mm not suitable for sanitary valves (ref. 14220/2, Art. 14230) and FixClip Valves




| ref. no. | description   | content |     | € |
|----------|---|---------|-----|---|
| 14218    | Calf drinking tray with 5 valves (Art. 149) and 5 Super Teats (Art. 147)  | 30 l 1  | 57  |   |
| 14201    | Calf drinking tray with 5 valves (Art. 149) and 5 latex teats (ref. 1454) | 30 l 1  | 57  |   |
| 14202    | Calf drinking tray with 5 Big Softy Teats (Art. 14141)                    | 30 l 1  | 57  |   |
| ref. no. | description   |         |     | € |
| 14215    | Calf drinking tray only, with large openings for Super and latex Teats    | 1       | 57  |   |
| 14203    | Calf drinking trough only, with small openings for Big Softy Teats        | 1       | 57  |   |
| 14910/5  | 5 Super Teats (Art. 147) with 5 valves (Art. 149)                         | 1       | -   |   |
| 14915/5  | 5 Latex Teats (Art. 1454) with 5 valves (Art. 149)                        | 1       | 400 |   |
| 14141/5  | 5 Big Softy Teats (Art. 14141)  | 1       | -   |   |
| 14890/5  | Seal Ring White, 5-pack   | 1       | -   |   |
| 14142    | Orange corner piece for Big Softy Teat (with valve), pack of 10           | 1       | -   |   |
| 14144    | White corner piece for Big Softy Teat (without valve), pack of 10         | 1       | -   |   |
| 14214    | Cover Hood for Multi Feeder   | 1/100   | -   |   |

# **Calf Feeder Tray Multi Feeder**

### with portioning

• with 5 portion compartments for the simultaneous provision of drinks to up to 5 calves
• with Big Softy Teats • makes animal surveillance easier during milk feeding • volume
per portion compartment: 3 litres • with rounded corners, thus very easy to clean • for
hanging on barn walls, feed barriers, fences, etc. • easy mounting and securing of the
trough thanks to elastic straps • ideal for Large Calf Hutch CalfHouse Premium 4/5 (ref. no.
14440) • stackable • easy to transport • acid-proof • food safe • dimensions (L x W x H):
810 x 430 x 380 mm • only suitable for Big Softy Teats









| ref. no. | description   |       | € |
|----------|---|-------|---|
| 14205    | Calf Drinking Tray Multi Feeder with 5 sections, without teats    | 1     |   |
| 14141/5  | 5 Big Softy Teats (Art. 14141)                                    | 1     |   |
| 14142    | Orange corner piece for Big Softy Teat (with valve), pack of 10   | 1     |   |
| 14144    | White corner piece for Big Softy Teat (without valve), pack of 10 | 1     |   |
| 14214    | Cover Hood for Multi Feeder                                       | 1/100 |   |

### Milk warmer tank 50 l

### Milk warmer

Specialist literature and studies indicate that the feeding of young calves has a marked effect on animal health, development and therefore the later performance of the animal. To achieve positive results, an in-depth knowledge on the part of the farmer and technical equipment are usually required. Our milk warmer provides the ideal support for calf rearing, especially for medium-sized businesses. It closes the gap between immersion heaters and mobile milk tanks with sophisticated equipment. Quickly and without much effort, up to 50 litres of milk or milk substitute mixture can be heated up.


- made from food-grade stainless steel
- easy cleaning thanks to the lid which can be fully opened
- with volume scale inside the tank
- water bath: separate inlet and outlet, viewing window to check fill levels

- · stepless thermostat
- pasteurisation possible
- 1" outlet with slider valve from the food industry
- with rod thermometer (food-safe)
- support feet optionally available

### Stirrer optionally available!

The powerful stirrer ensures the clump-free stirring of milk exchangers. By briefly switching the mixer on during the heating of fresh milk, the heating time can be shortened. The cover with integrated mixer can be easily placed on the






• 1,000 rpm • 370 W • ready to connect • with opening for thermometer



technical data Dimensions: Height:

| ref. no. | description             |      | € |
|----------|-------------------------|------|---|
| 141450   | Calf's milk warmer 50 l | 1    |   |
| 141461   | Cover with stirrer      | 1    |   |
| 141453   | Rod thermometer         | 1/10 |   |
| 141462   | Tripod                  | 1    |   |





# **Calzogol Bolus**

### Calcium bolus (milk fever)

Cows with optimum calcium supply have a better start to lactation, are healthier and produce more milk. • very high levels of fast and slow availability calcium (45 g) and vitamin D3 (40,000 I.E.) per bolus! • calcium sources with varying release rates supply the cow evenly with calcium • very well tolerated by membranes – no irritation of the mouth, esophagus and rumen • no caustic calcium chloride • easy application and economical – one bolus per dose is enough!

Feeding recommendation: Administer one bolus with the applicator as per the instructions when calving. If required, administer a second bolus approx. 12 hours after birth.

1/8



### **Ket-o-Vital® Bolus**

175 g

### **Energy Bolus (Ketosis)**

15980

Healthy cows become pregnant quicker and provide more milk. • bolus that works on various physiological levels – liver - rumen - immune system • The glucoplastic substances have a positive effect on energy metabolism. The risk of ketosis / acetonaemia decreases. Very high milk yield, birth problems, stress, heat and obesity at the time of birth are classical risk factors for ketosis • safe dosage and application The animals have more appetite, are fitter and recover faster

Feeding recommendation: Administer two boluses shortly after calving using a bolus applicator as per the instructions. If required, administer another bolus 12 hours after calving.





# **Fertilgol Bolus**

### Beta Carotene Bolus (fertility)

A quick pregnancy shortens the calving interval and improves economic success. • for male and female breeding animals just before and during the covering or insemination period • supports a successful embryo transfer (recipient and donor animals) • the high beta carotene content aids the corpus luteum formation, colostrum quality, the oestrus cycle and sperm quality • a well-developed corpus luteum has a positive influence on the embryonic survival rate • easy and safe application through the even release of beta carotene, vitamins and trace elements over a period of min. 20 days • the release rate has been scientifically confirmed

### Feeding recommendation:

Female cows: Administer the first bolus 30 days before insemination. Administer the second bolus shortly before or after insemination

Stud bulls: Administer one bolus every 20 - 30 days during breeding season. The bolus dissolves in 20 days in the rumen

long-term bolus

| ref. no. | Weight / bolus | <b>\       </b> |     | € |
|----------|----------------|-----------------|-----|---|
| 15983    | 95 g           | 8               | 1/8 |   |







# **Vitalgol Bolus**

### Mineral Vitamin Bolus (Vitality)

Well-nourished animals have the best conditions for good growth, vitality and fertility • for male and female cattle • the long-term bolus releases vitamins and trace elements safely and evenly over a period of at least 90 days The release rate has been scientifically confirmed • a constant supply of essential vitamins and trace elements cannot be safely guaranteed with conventional feed, especially in pastures / hill farms / mountain farms. The solution is the Vitagol long-term bolus. • Individual animals in a herd can be targeted for a boost of vitamins and trace elements

### Feeding recommendation:

Young cattle < 300 kg live weight: one bolus every 3 months, administer using a bolus applicator as per the instructions.

Cattle > 300 kg: two boluses every 3 months, administer using a bolus applicator as per the instructions.







| ref. no. | Weight / bolus | <b>4</b> Ⅲ |     | € |
|----------|----------------|------------|-----|---|
| 15981    | 110g           | 8          | 1/8 |   |

Dietary mineral feed for cattle for the long-term supply of trace elements and vitamins to grazing animals – long-term bolus.





# **Bufferlyt Bolus**

### Electrolyte bolus

Use for diarrhoea, lack of appetite and reluctance to drink • The calves are more stable and recover more quickly. • Sodium bicarbonate is a very effective buffer. The use of buffers helps to resist excess acidity. Excess acidity is often the reason why calves are weak and dull and have no desire to drink • Lost electrolytes are effectively replaced. This protects from the dehydration effects of diarrhoea, transport stress and heat • stress-free and safe administration Administration can also be done without an applicator. Simply place the bolus lengthways on the base of the tongue using your hand. The calf will swallow the bolus with no problems • applicator not included

Feeding recommendation: Immediately administer one bolus as per the instructions at the first signs of diarrhoea. Then administer one bolus after each liquid meal for 2 - 3 days.



Supplementary feed with sodium bicarbonate, an effective buffer substance.



| ref. no. | description                    | Weight / bolus | ĀⅢ |      | € |
|----------|--------------------------------|----------------|----|------|---|
| 15984    | Bufferlyt Bolus                | 13 g           | 15 | 1/12 |   |
| 15985    | Applicator for Bufferlyt Bolus | -              | -  | 1/12 |   |



# **Dispenser for Udder Paper**

- for (udder) paper rolls with centre pull cover made from sturdy plastic housing (ABS)
- with transparent and lockable cover with integrated tear-off edge easy wall mounting
- dimensions (H x W x D): 255 x 250 x 358 mm weight: approx. 1200 g fits Kerbl UdderoClean udder paper (800 and 1000 sheets) and UdderoClean Air Premium (350 sheets)
- · supplied without paper



Available from April 2018!

# **Dispensing Pump**


- ullet suitable for 10 250 ml pumps ullet suitable for 1-litre bottles of milk cell test reagent N from GEA ullet 3 ml pumping volume per stroke ullet with rotating valve
- made from polypropylene plastic



# **Spray Nozzle Super Jet**

- anti-slip coating variable adjustable spray or concentrated jet
- flow rate regulated separately suitable for water temperatures up to 35 °C 4-6 bar available 50 l/min water flow rate
- with hose connector





**KERBL** 


| ref. no. |      | € |
|----------|------|---|
| 151871   | 1/12 |   |

Available from April 2018!

### **Rinser Twist Jet**

• anti-slip coating • variable adjustable spray or concentrated jet • suitable for water temperatures up to 35 °C • can be used up to pressures of max. 4 bar • 38-47 l/min water flow rate • with hose connector





|          |      | - |
|----------|------|---|
| ref. no. | ₩    | € |
| 151872   | 1/30 |   |

# **Dip Cup Premium NonReturn**

- a return flow protection prevents used dip material from flowing back into the bottle clean dip material, full effect on the cow teats specially developed splash guard with draining to an overflow chamber: less overflow, less waste
- soft plastic bottle for low-fatigue working even for a large animal population
- cup capacity 300 ml practical belt hook







The Original

# **Dip Cup Premium FoamExpert**

with special foaming sleeve insert in the container • quick, uniform foaming via just compression • easy to disassemble for cleaning • soft plastic bottle for low-fatigue working even for a large animal population • cup capacity 300 ml
 practical belt hook





# **Dip Cup Premium NonReturn Twin**

• excellent for light applications of film-forming or "barrier dips" with high viscosity • double hose accepts the same amount of dip medium, but only requires half the power for pressing • a return flow protection prevents used dip material from flowing back into the bottle • clean dip material, full effect on the cow teats • specially developed splash guard with draining to an overflow chamber: less overflow, less waste • soft plastic bottle for low-fatigue working even for a large animal population • cup capacity 300 ml • practical belt hook



for viscous media

# **Dip Cup Premium NonReturn Cross**

• cross dip cup with return flow protection • suitable for cows, goats and sheep • dip loss is avoided due to the unique dip medium container with a drip guard edge • with a double hose so that viscous, film-forming media can be used • soft plastic bottle for low-fatigue working even for a large animal population • cup capacity 300 ml

· practical belt hook



Win Dippel

Foam Dippel







for viscous media





# **Kerbl milk filters**

Our company has been producing both the sewn and thermally bonded milk filter socks using our own high-tech production machinery since 2017, in order to further optimise the product quality and to be able to react more flexibly to customer requests.


We also produce disc filters for cans under the Kerbl own-brand 'Sana', as well as milk filter socks. Sana has stood for the highest quality and reliability in milk filtration for decades and is also well-known far beyond the borders of Germany.

### Sana Premium

Kerbl has also developed a premium version for the SANA brand, in order to meet the growing demands in milk production. Thanks to its optimised fibre distribution, the premium filter offers even higher tensile strength and finest filtration while still providing the necessary permeability for raw milk. This makes the filter especially suitable for large amounts of milk and the highest standards.



fibre distribution and permeability.



# Sana Premium Milk Filter

sewn

- sewn for vacuum systems high-quality, food-safe nonwoven fabric
- high tensile strength and finest filtration especially suitable for large amounts of milk and the highest standards
- milk taste and quality is protected







| ref. no. | width    | length | use for  | <b>∤</b> |     | € |
|----------|----------|--------|--|----------|-----|---|
| 46731    | 57/60 mm | 250 mm | GEA / Westfalia, Miele (Meltec), Lister, Lemmer Fullwood | 250      | 1/4 |   |
| 46733    | 57/60 mm | 320 mm | DeLaval, Flaco, Manus, Gascoigne-Melotte, Utina          | 250      | 1/4 |   |
| 46734    | 57/60 mm | 455 mm | GEA / Westfalia, Meltec                                  | 250      | 1/4 |   |
| 46735    | 57/60 mm | 480 mm | System Happel  | 250      | 1/4 |   |
| 46736    | 57/60 mm | 500 mm | Meltec   | 250      | 1/4 |   |
| 46737    | 57/60 mm | 530 mm | GEA (MIone), Lemmer Fullwood, Packo                      | 250      | 1/4 |   |
| 46738    | 57/60 mm | 620 mm | DeLaval, Boumatic, Flaco, Manus, DEC, Gascoigne-Melotte  | 250      | 1/4 |   |
| 46739    | 75/78 mm | 455 mm | SAC  | 200      | 1/5 |   |
| 46740    | 75/78 mm | 620 mm | Lely (Melkroboter), GEA, Boumatic, SAC                   | 200      | 1/5 |   |
| 46741    | 75/78 mm | 820 mm | GEA, Impulsa, Meltec                                     | 200      | 1/5 |   |
| 46742    | 95/98 mm | 610 mm | DeLaval (carousel)                                       | 200      | 1/5 |   |

# Sana Milk Filters sewn

- 75 g for vacuum systems high-quality, food-safe nonwoven fabric milk taste and quality is protected





| ref. no. | width    | length | use for  | ₩   |     | € |
|----------|----------|--------|--|-----|-----|---|
| 46681    | 57/60 mm | 250 mm | GEA / Westfalia, Miele (Meltec), Lister, Lemmer Fullwood | 250 | 1/4 |   |
| 46683    | 57/60 mm | 320 mm | DeLaval, Flaco, Manus, Gascoigne-Melotte, Utina          | 250 | 1/4 |   |
| 46684    | 57/60 mm | 455 mm | GEA / Westfalia, Meltec                                  | 250 | 1/4 |   |
| 46685    | 57/60 mm | 480 mm | System Happel  | 250 | 1/4 |   |
| 46686    | 57/60 mm | 500 mm | Meltec   | 250 | 1/4 |   |
| 46687    | 57/60 mm | 530 mm | GEA (MIone), Lemmer Fullwood, Packo                      | 250 | 1/4 |   |
| 46688    | 57/60 mm | 620 mm | DeLaval, Boumatic, Flaco, Manus, DEC, Gascoigne-Melotte  | 250 | 1/4 |   |
| 46689    | 75/78 mm | 455 mm | S.A.C.   | 200 | 1/5 |   |
| 46690    | 75/78 mm | 620 mm | Lely (Melkroboter), GEA, Boumatic, SAC                   | 200 | 1/5 |   |
| 46691    | 75/78 mm | 820 mm | GEA, Impulsa, Meltec                                     | 200 | 1/5 |   |
| 46692    | 95/98 mm | 610 mm | DeLaval (carousel)                                       | 200 | 1/5 |   |

# Sana Milk Filters bonded

• 75 g • for vacuum systems • high-quality, food-safe nonwoven fabric

• milk taste and quality is protected





| ref. no. | width    | length | use for  | <b>∤</b> |     | € |
|----------|----------|--------|--|----------|-----|---|
| 46670    | 57/60 mm | 250 mm | GEA / Westfalia, Miele (Meltec), Lister, Lemmer Fullwood | 250      | 1/4 |   |
| 46671    | 57/60 mm | 320 mm | DeLaval, Flaco, Manus, Gascoigne-Melotte, Utina          | 250      | 1/4 |   |
| 46672    | 57/60 mm | 455 mm | GEA / Westfalia, Meltec                                  | 250      | 1/4 |   |
| 46673    | 57/60 mm | 500 mm | Meltec   | 250      | 1/4 |   |
| 46674    | 57/60 mm | 530 mm | GEA (MIone), Lemmer Fullwood, Packo                      | 250      | 1/4 |   |
| 46675    | 57/60 mm | 620 mm | DeLaval, Boumatic, Flaco, Manus, DEC, Gascoigne-Melotte  | 250      | 1/4 |   |

# **Sana Disc Filters**

• for milk strainer • high-quality, food-safe nonwoven fabric





| ref. no. | Ø      | <b>4</b> Ⅲ |      | € |
|----------|--------|------------|------|---|
| 46752    | 115 mm | 200        | 1/60 |   |
| 46753    | 120 mm | 200        | 1/60 |   |
| 46754    | 125 mm | 200        | 1/60 |   |
| 46755    | 140 mm | 200        | 1/60 |   |
| 46756    | 160 mm | 200        | 1/35 |   |
| 46757    | 170 mm | 200        | 1/35 |   |
| 46758    | 180 mm | 200        | 1/30 |   |
| 46759    | 190 mm | 200        | 1/30 |   |
| 46760    | 200 mm | 200        | 1/30 |   |
| 46761    | 220 mm | 200        | 1/30 |   |
| 46762    | 240 mm | 200        | 1/10 |   |
| 46763    | 270 mm | 200        | 1/10 |   |
|          |        |            |      |   |



# Sana Disc Filters with Hole

• for milk strainer • high-quality, food-safe nonwoven fabric





| ref. no. | Ø      | 4   |      | € |
|----------|--------|-----|------|---|
| 46770    | 220 mm | 100 | 1/30 |   |
| 46771    | 300 mm | 100 | 1/10 |   |

# **Hygiene Sleeve Protector**

The tight-fitting wrist cuff makes sure that no water, etc. can get into the sleeve protector. Scissors can be used, if necessary, to shorten the cuff to customise

• made of pure polyurethane (TPU) • food safe • waterproof (to 3000 mm water column) • detectable • chemical-resistant and can be disinfected and sterilised • extremely tear- and abrasion-resistant • flexible in the cold down to -20 °C • machine-washable up to 95 °C • length: 50 cm • in pairs





| ref. no. | size  |      | € |
|----------|-------|------|---|
| 15609    | S/M   | 1/20 |   |
| 15610    | I /YI | 1/20 |   |

Size S / M is ideal for wrists greater than 14 cm in diameter. Size L / XL is ideal for wrists greater than 18 cm in diameter. You can cut to fit with scissors.

# Disposable Gloves Nitrile Premium

• especially suitable as milking gloves • 30 cm long for comfortable protection • thickness: min. 0.20 mm ~ 8 mil • weight of size M: 12.0 - 13.0 g/piece • non-sterile • for single-use only • 1.5 AQL (quality standard) • ambidextrous • latex and powder-free • free from allergy inducing thiurames, thiazoles and latex proteins • food safe • for the toughest conditions • compliant with EN 455 • EN 374/1 certified (protection from chemicals and micro-organisms) • 50 pieces per dispenser box



| ref. no. | size |      | $\blacksquare$ | € |
|----------|------|------|----------------|---|
| 15325    | S    | 1/20 | 300            |   |
| 15326    | М    | 1/20 | 300            |   |
| 15327    | L    | 1/20 | 300            |   |
| 15328    | XL   | 1/20 | 300            |   |
| 15329    | XXL  | 1/20 | 300            |   |



# Teat Cup Brush

• 3-level bristle spiral • staggered bristle length to 59 mm diameter • with plastic handle • boil-proof up to 100 °C • acid-proof

| ref. no. | length |      | € |
|----------|--------|------|---|
| 151785   | 50 cm  | 1/50 |   |

# Hygienic hand disinfectant liquid\*

• alcohol rub-on preparation for fast disinfection without water • prevents the spread of bacteria (incl. salmonella), fungi and lipophilic viruses • confirmed effect as per European standard (EN 1500) against bacteria and fungi • assessed effect as per EN standard 1276 against salmonella enteritidis and salmonella typhimurium • cares for the skin with refattening agents • in a handy dispenser bottle

| ref. no. | content |      | € |  |
|----------|---------|------|---|--|
| 151179   | 500 ml  | 1/10 |   |  |



<sup>\*</sup> Take care when using disinfectants. Always read the label and product information before use!



# **Universal Bandage Kompressa**

• elastic compression bandage with medium stretch • for fixed dressings, binding splints, support and relief bindings, compacting bindings for first aid and follow-up care and ointment dressings • material composition: 67 % cotton, 25 % polyamide, 8 % polyurethane • supplied without clips • stretched, 5 m length • as per DIN 61 632-S standard



| ref. no. | description                 | length | width | MQ |      | € |
|----------|-----------------------------|--------|-------|----|------|---|
| 16473    | 10 pieces per clinical pack | 5 m    | 8 cm  | 1  | 1/24 |   |
| 16474    | 10 pieces per clinical pack | 5 m    | 10 cm | 1  | 1/24 |   |

# **Short-Stretch Bandages Stretchino**

- long-life elastic short-stretch bandage for very strong compression with high working pressure and low resting pressure stretches about 50 % hypoallergenic non-ageing
- washable at 60 °C



| ref. no. | description                           | length | width | MQ |          | € |     |
|----------|---------------------------------------|--------|-------|----|----------|---|-----|
| 16457    | 10 pieces, individually in cellophane | 5 m    | 8 cm  | 10 | 1/10/240 |   |     |
| 16458    |                                       | 5 m    | 8 cm  | 1  | 1/24     |   | NEW |

# **Veterinary Bandage Klaudia**

• non-elastic special bandage made of a cotton/viscose mixture • resistant, non-ageing and kind to the skin



| ref. no. | description                 | length | width | MQ |      | € |     |
|----------|-----------------------------|--------|-------|----|------|---|-----|
| 16472    | 10 pieces per clinical pack | 6 m    | 6 cm  | 1  | 1/24 |   |     |
| 16451    | 10 pieces per clinical pack | 6 m    | 8 cm  | 1  | 1/24 |   | NEW |

### **Abrasive Disc Wide**

• hoof plate made of twisted steel dish with carbide assembly • excellent value for money

### Available from April 2018!

| ref. no. | Ø      | description      | SB |      | € |
|----------|--------|------------------|----|------|---|
| 16377    | 115 mm | 40 grit, 1-sided | -  | 1/50 |   |
| 16353    | 125 mm | 40 grit, 1-sided | -  | 1/50 |   |
| 16354    | 150 mm | 40 grit,         | -  | 1/50 |   |

# Wire Saw Aesculap

- extra strong wire saw for birth assistance and dehorning
- professional quality from Aesculap

| ref. no. | length |   | € |
|----------|--------|---|---|
| VF676    | 10 m   | 1 |   |





### **Technobase 2CB New Formula**

Technobase 2CB New Formula is the ultimate two-component adhesive for professional use in modern hoof care. The blue colouring immediately shows the correct mixture when squeezing.

The new formula has been optimised for the parameters of curing speed, viscosity and hardness after polymerisation in comparison with standard two-component adhesives.

• the adhesive becomes as hard as glass, optimally adhering to hoof and block • the liquidity of the adhesive mix has been designed to allow working at both 45 ° and 90 ° angles • the hoof can bear full weight again after approx. 2 minutes (if stored correctly over 15° C) • the high-quality 200 ml cartridge, which can be opened and closed again with just a few actions and no need for tools, guarantees maximum reliability in relation to hoof care • the correct attachment of the special mixing cannulas is made child's play thanks to the specific accepting bolts, ensuring the correct mixing ratio with minimum waste • bonds powerfully and permanently to wood and rubber blocks • even easier to use thanks to the easy-to-handle and recloseable cartridge

Technobase 2CB





| Reaction time at ambient temperature: |
|---------------------------------------|
|---------------------------------------|

| > 25 °C    | approx. 15 seconds |  |
|------------|--------------------|--|
| 15 – 25 °C | 20 seconds         |  |
| 5 – 15 °C  | 25 seconds         |  |
| < 5 °C     | approx. 35 seconds |  |

| ref. no. | description                                      | content   |      | € |
|----------|--|-----------|------|---|
| 16282    | Cartridge  | 200 ml    | 1/12 |   |
| 16273    | Technobase 2CB mixer cannulas for item no. 16282 | 12        | 1/10 |   |
| 16285    | Farmer Set                                       | 4 x 25 ml | 1    |   |
| 16286    | Cartridge  | 25 ml     | 1/15 |   |
| 16284    | Dispensing gun                                   | -         | 1/12 |   |


# **Thermal Container HeatBox**

The solution to problems using two-component adhesives for hoof care in winter! HeatBox offers the perfect way to keep two cartridges at the correct temperature during use in stables, thanks to the critical temperature property of its chemistry.

### Additional product properties:

- one heat chamber each for cartridges in the pistol and for spare cartridges (only fits Technobase 2CB dosing pistol item. no. 16284) fits all common 200 ml cartridges such as Technobase 2CB
- constant temperature in the chamber of 20 °C thanks to integrated thermostat
- incl. metal bracket for attaching to the hoof stand or bar/tube with vehicle plug and power pack for connection to a 230 V power supply input: 12 V / 50/60 Hz

| ref. no. |     |     | € |
|----------|-----|-----|---|
| 16278    | 1/8 | 128 |   |



16273

# Hoof Shoe Tubbease™

Tubbease<sup>™</sup> was developed in New Zealand with the aim to create a breathable treatment shoe for problem horse hooves (e.g. sole ulcers). The supplied Velcro tapes mean Tubbease<sup>™</sup> is easy to attach to the horse's leg. Tubbease<sup>™</sup> is available in three sizes.

The benefits of Tubbease™:

• air can escape upwards meaning no heat or humidity is trapped within the shoe • the rubber-coated base reliably prevents moisture from entering and simultaneously ensures that the treatment fluid remains on the hoof

• the optimum climate within the shoe means the hoof retains its natural strength • the thick EVA insole reduces pressure pain for the horse (e.g. with sole ulcers) and extends the life of Tubbease<sup>™</sup> • various remedies to treat abscesses, thrush, hoof injuries, hoof outbreaks etc. can be used with Tubbease<sup>™</sup> • Tubbease<sup>™</sup> design is protected (NZ 417646)



| ref. no. | size | colour | Ø     |      | € |
|----------|------|--------|-------|------|---|
| 3210560  | M    | red    | 14 cm | 1/20 |   |
| 3210561  | L    | blue   | 15 cm | 1/20 |   |
| 3210562  | XL   | orange | 16 cm | 1/20 |   |

| ref. no. | description         | size | colour |      | € |
|----------|---------------------|------|--------|------|---|
| 3210563  | Replacement Velcro  | -    | -      | 1/12 |   |
| 3210564  | EVA insole Tubbease | М    | red    | 1/20 |   |
| 3210565  | EVA insole Tubbease | L    | blue   | 1/20 |   |
| 3210566  | EVA insole Tubbease | XL   | orange | 1/20 |   |



# **Treatment Shoe for Hooves**

Durable and robust treatment shoe made of canvas with two bands. Ideal for treating horse or cattle hooves with ointments or solutions.

- with 2 bands for knotting
- strong plastic sheet on the inside to allow the treatment solution to work effectively
- standard size (15 x 30 cm)





| ref. no. |      | € |
|----------|------|---|
| 16143    | 1/50 |   |

# Adhesive Claw Bandage VetTape

 $\bullet$  with highly adhesive rubber glue  $\bullet$  excellent adhesive properties  $\bullet$  well tried as hoof dressing  $\bullet$  porous

| ref | f. no. | colour | length | width |      | € |
|-----|--------|--------|--------|-------|------|---|
| 16  | 388    | white  | 50 m   | 50 mm | 1/12 |   |
| 16  | 390    | black  | 50 m   | 50 mm | 1/12 |   |

... recommended from veterinarians!

NEW



# **Aesculap Precision Adjusting Aid for Torqui Favorita**

Every Favorita clipping head is child's play to adjust with this torque key. Benefits of the Torqui at a glance:

- precise basic adjustment of the plate pressure
- increased clipping head life thanks to longer intervals between regrinding
- consistent edge-retention
- easy to handle
- no prior knowledge needed
- · small, easy to handle, maintenance-free
- · precision instrument engineered in Germany
- compatible with all Favorita clipping heads
- all Favorita clipping heads can be retrofitted with an appropriate knurled screw



| ref. no. | description  |       | € |
|----------|--|-------|---|
| GT142    | Precision adjusting aid for Torqui, Favorita system  | 1     |   |
| GT141    | Knurled screw for Torqui, Favorita system, 10 pieces | 1/100 |   |





For perfect plate pressure!

# **Aesculap Precision Adjusting Aid Torqui Econom**

Every Econom clipping head is child's play to adjust with this torque key.

Benefits of the Torqui at a glance:

- precise basic adjustment of the plate pressure
- increased clipping head life thanks to longer intervals between regrinding
- consistent edge-retention
- easy to handle
- no prior knowledge needed
- · small, easy to handle, maintenance-free
- · precision instrument engineered in Germany
- suitable for all Econom cattle and horse clippers
- all Econom shaving heads can be retrofitted with the knurled screw GT147





| ref. no. | description                                       |       | € |  |
|----------|---|-------|---|--|
| GT146    | Precision adjusting aid for Torqui, Econom system | 1     |   |  |
| GT147    | Knurled screw for Torqui, Econom system           | 1/500 |   |  |





# **Aesculap Battery Clippers Bonum**

The new cordless clippers from Aesculap, fitted with lithium-ion batteries and a sleek and ergonomic design. The Bonum is also a perfect fit for women's hands and boasts low weight, low noise and long battery life.







The Bonum is also fitted with an intelligent lithium-ion battery system. On the one hand, the battery technology protects the device from overheating and switches it off until it has cooled when the battery temperature reaches >50°C. On the other hand, the charger provides information on the battery status with two LED displays:

- extremely light, just 900 g incl. batter and shaving blade
- just 40 mm diameter and 12.5 cm in circumference in the grip area, therefore also great for small hands
- volume / frequency pleasant for your horse
- very short and handy at 295 mm in length
- · very well balanced
- · powerful and long-lasting
- lithium technology so no memory effect
- battery from tool professionals
- electronic push button recessed in the housing means no more accidental switching the machine on or off when handling



| technical data       |                     |  |
|----------------------|---------------------|--|
| Weight with battery: | 900 g               |  |
| Dimensions (W/H/L):  | 29.5 x 7.5 x 7.8 cm |  |
| Run time:            | 80 min              |  |
| Charging time:       | 55 min              |  |
| DC motor:            | 10.8 V              |  |
| Sound level:         | 65 db (A)           |  |
| Stroke rate:         | 2500 rpm            |  |



| ref. no. | description   | colour |      | € |
|----------|---|--------|------|---|
| GT644-BL | Battery Clippers Bonum Cattle, incl. 1 battery, GT501 / GT502 | blue   | 1/6  |   |
| GT654-BL | Battery Clippers Bonum Horse, incl. 1 battery, GT505 / GT502  | blue   | 1/6  |   |
| GT654-RO | Battery Clippers Bonum Horse, incl. 1 battery, GT505 / GT502  | pink   | 1/6  |   |
| GT646-BL | Battery Clippers Bonum Cattle, incl. 2 battery, GT501 / GT502 | blue   | 1/6  |   |
| GT656-BL | Battery Clippers Bonum Horse, incl. 2 battery, GT505 / GT502  | blue   | 1/6  |   |
| GT656-RO | Battery Clippers Bonum Horse, incl. 2 battery, T505 / GT502   | pink   | 1/6  |   |
| GT641    | Replacement battery for Bonum                                 | -      | 1/14 |   |

# **Aesculap Battery-Operated Clipper Econom CL for Sheep**

Aesculap is one of the first companies in the world to market a wireless sheep clipper. Aesculap used their expertise and engineering skills to thoroughly meet the special demands made on batteries when sheep shearing. The new sheep clipper does of course boast the prestigious Aesculap quality down to the last detail.





The electronic controller controls the power flow from battery to machine. When more power is needed, the controller automatically increases the performance and lowers it if necessary. This optimises battery life and ensures the quality of the shearing remains consistently good.

Using a brushless direct current motor (EC motor) has the advantage of less heat development, leading to longer battery service life and thus longer overall service life for the clipper. The lack of carbon brushes therefore provides a practically wear-free drive.

- ideal for clipping the tails of sheep or for shearing cattle with wool-like coats
- huge pulling power, like a cable-operated sheep clipper
- high shearing speed, glides perfectly through the coat
- low weight, fatigue-free handling
- electronic push button recessed in the housing means no more accidental switching the machine on or off when handling
- · powerful EC motor
- very well balanced

GT821

- powerful and long-lasting
- lithium technology so no memory effect
- effortlessly achieves 2700 rpm
- Aesculap cutting plates from the Made in Germany Econom series



Intelligent battery technology: provides just enough power that's needed and switches to "standby" mode after 1 h of inactivity (increases the lifespan of the battery).

| technical data        | " # F                               |
|-----------------------|-------------------------------------|
| Clipping head system: | Shearing blade set                  |
| Drive:                | DC motor, approx. 2,700 strokes/min |
| Gear box:             | Spur gear                           |
| Battery technology:   | 3500 mAh, lithium-ion               |
| Weight:               | approx. 1470 g                      |
| Sound pressure level: | approx. 72 dB                       |
| Run time:             | approx. 70 min                      |
| Charging time:        | approx. 80 min                      |
|                       |                                     |
| supplied package:     | 1 Econom CL Machine                 |
|                       | + 1 charger                         |
|                       | + Li-ion battery (GT821)            |
|                       | + 1 upper blade (GT578)             |
|                       | + 1 lower blade (GT588) (3.5 mm)    |
|                       | + 1 Aesculap oil (GT604)            |
|                       |                                     |

|          | + 1 upper blade (GT578) + 1 lower blade (GT588) (3.5 mm) + 1 Aesculap oil (GT604) + 1 handy and solid plastic case |    |   |   |
|----------|--|----|---|---|
| ref. no. | description  | MQ |   | € |
| GT824    | Battery-Operated Clipper Econom CL incl. 1 Battery   | 1  | 1 |   |

Spare Battery for Clipper Econom CL





# **Scratch Brush HAPPYCOW MiniSwing**

# for calves and goats

The HAPPYCOW MiniSwing cleaning machine rotates in any direction and almost every angle. The vertical pendulum brush reaches almost any body part, head and rump especially are thoroughly cleaned.

The HAPPYCOW MiniSwing scratch brush is suitable for calves from 3 months of age and adult goats. One brush is designed for max. 60 calves or max. 50 goats.

The HAPPYCOW MiniSwing is automatically activated for approx. 60 seconds by slightly lifting the brush from the animals. The changing direction of the brush after ever activation ensures even wear of the brushes. The torque safety shutdown stops the brush when it encounters too much resistance, ensuring safety in the stable.




| technical data    |                                    |
|-------------------|------------------------------------|
| Voltage:          | 230 V, 50 / 60 Hz                  |
| Output:           | 0.25 kW                            |
| Speed:            | 26.8 rpm                           |
| Weight:           | 48 kg                              |
| Dimensions:       | 30 cm x 125 cm x 80 cm (W x H x D) |
| Protection type:  | IP54                               |
| Bristle material: | Polypropylene (PP)                 |

| ref. no. | description                      |   |   | € |
|----------|----------------------------------|---|---|---|
| 18890    | Scratch Brush HAPPYCOW MiniSwing | 1 | - |   |
| 18891    | Spare Brush MiniSwing            | 1 | - |   |

### **Scratch Brush**

• ensures ideal fur cleaning and care • head and throat in particular can be cleaned • for mounting in stables • bristle length 5 cm • bristle material: polyamide (PA)







# **Hay Bell for Round Bales**

• for round bales with max. diameter x height of 160 cm x 125 cm or 130 x 135 cm • shatter-proof, frost-proof plastic material with built-in UV protection • sturdy construction • with animal-friendly and non-damaging food openings • water-removing rain channels over the food openings • with integrated carrying handle, suitable for front loader forks • with integrated fixing eyelets for fixing the base to the hay bell • base (available separately) for dry storage of the bales; can be locked for transportation with the hay bell



14558

| ref. no. | description  |      |    | €   |
|----------|--|------|----|-----|
| 14557    | Hay bell with 5 large food openings for cattle and horses                | 1    | 6  | - B |
| 14558    | Hay bell with 10 small food openings for sheep, goats, calves and ponies | 1    | 6  | - B |
| 14559    | Base for hay bell  | 1    | 25 |     |
| 14556    | Anchoring for Hay Bell item no. 14557, item no. 14558 and base           | 1/10 | -  |     |

# **Square Rack Hobby**

- 8 feeding places
- suitable for round and rectangular bales up to 1.4 m in length or diameter
- hot-dip galvanised
- 1 square tubular support
- 2 sides can easily be opened for filling
- height-adjustable runners (adjustable to the animal's size)
- three-point attachment
- very little food loss
- supplied as a construction kit including circumferential roof edge protection, three-point safety clip
- internal trough dimensions: approx. 1.45 x 1.45 m
- complete dimensions L x W x H: approx. 1.5 x 1.5 x 2.4 m



14557

### Please note separate freight costs!

| ref. no. |   |   | € |  |
|----------|---|---|---|--|
| 291300   | 1 | 6 |   |  |












# **Feed Storage Rack Metal**

• high-quality sturdy feed storage rack made from galvanised metal for wall mounting • the design allows the horse to eat appropriately and slowly • approx. 90 L capacity | provides a daily ration of raw food • the grid is pressed against the food by the rotary hinge when the horse eats, so it receives small portions and is engaged for a long period • raw food can be easily refilled by lifting the grid from the front or from behind as required and through an opening in the box partition • large opening at the bottom for easy removal of uneaten food • weight: approx. 14 kg • comes disassembled as a kit • incl. assembly instructions, easy assembly





| ref. no. | lxwxh           |   |    | € |
|----------|-----------------|---|----|---|
| 32706    | 60 x 47 x 53 cm | 1 | 20 |   |



# **Feeding Trough semicircle**

Feeding trough in half-circle shape without rough edges! Lightweight but very sturdy!

• feeding trough made of Polyethylene • half-circle shape to be mounted at straight walls • with anti-waste edge • rounded section in the inner side for more hygiene • with cleaning plug • dimensions  $55 \times 35 \times 17.7 \text{ cm}$ 

| ref. no. | content |   |    | € |
|----------|---------|---|----|---|
| 324825   | 25 l    | 1 | 66 |   |



# Tyre Trough

• high-quality sturdy feeding trough made from polyethylene • ideal for feeding horses in large and/or open stables • for proper feeding, as horses can feed in a natural stance • positioned for 175/14 tyres or larger, supplied without tyres


| technical data     |         |
|--------------------|---------|
| Interior diameter: | 35.0 cm |
| Exterior diameter: | 51.0 cm |
| Overall height:    | 19.5 cm |

| ref. no. | content |   |     | € |
|----------|---------|---|-----|---|
| 324826   | 15 l    | 1 | 105 |   |



# **Lick Holder square**

- plastic no sharp edges dimensions: approx. 202 x 206 mm
- $\bullet$  inside dimensions: 191 x 194 mm  $\bullet$  also suitable for 15 kg salt stones





# **Feeding Bowl**

- universal bowl for food impact- and temperature-resistant plastic food safe
- approx. 6 litres capacity bowl and lid can be printed on request



Available in customer-specific composition. Note the instructions at the end of the catalogue.

| ref. no. | description          | colour     |        | $\blacksquare$ | € |     |
|----------|----------------------|------------|--------|----------------|---|-----|
| 324811   | Feeding Bowl         | grey       | 1/5    | 500            |   |     |
| 324812   | Feeding Bowl         | green      | 1/5    | 500            |   |     |
| 324815   | Feeding Bowl         | aquamarine | 1/5    | 500            |   | NEW |
| 324816   | Feeding Bowl         | rosé       | 1/5    | 500            |   | NEW |
| 324820   | Lid for Feeding Bowl | white      | 1/5/50 | 600            |   | =   |
|          |                      |            |        |                |   |     |



# all-Purpose Bucket

• heavy-duty model





Available in customer-specific composition. Note the instructions at the end of the catalogue.

| ref. no. | description          | colour           | content |      |     | € |     |
|----------|----------------------|------------------|---------|------|-----|---|-----|
| 29881    | All-Purpose Bucket   | olive green      | 12 l    | 1    | 350 |   |     |
| 298800   | All-Purpose Bucket   | blue transparent | 12 l    | 1    | 350 |   | NEW |
| 298801   | All-Purpose Bucket   | transparent pink | 12 l    | 1    | 350 |   | NEW |
| 29935    | Lid for Bucket 29881 | black            | -       | 1/30 | 720 |   | •   |

# FlexBag Flexible Trough

• trough made from sturdy but extremely flexible plastic • can be used anywhere, in the pasture and in the stable, as feed, transport or grooming tool tub, as well as at home or in the garden • two handles for easy transport

| ref. no. | content | colour |      |     | € |
|----------|---------|--------|------|-----|---|
| 323530   | 12 l    | green  | 1/10 | 480 |   |
| 323531   | 12 l    | purple | 1/10 | 480 |   |
| 323532   | 12 l    | red    | 1/10 | 480 |   |
| 323533   | 28 l    | blue   | 1/10 | 240 |   |
| 323534   | 28 l    | yellow | 1/10 | 240 |   |
| 323535   | 28 l    | red    | 1/10 | 240 |   |
| 323536   | 42 l    | blue   | 1/10 | 200 |   |
| 323537   | 42 l    | yellow | 1/10 | 200 |   |
| 323538   | 42 l    | red    | 1/10 | 200 |   |
| 326197   | 60 l    | red    | 1/10 | 400 |   |
| 326198   | 60 l    | blue   | 1/10 | 400 |   |



# **Water Trough**

Robust special material

• extremely break-proof and retains its shape • UV and frost resistant

### Carefully thought-out design

• stable internal wall curving inwards • oval shape allows easy loading into a small transporter • large outlet for rapid drainage (outlet Art. 16601 included in supplied package) • water connection and float valve protected from animals • easy cleaning thanks to smooth surfaces and rounded edges - no inaccessible areas • floor anchoring optionally available (accessories not included in the scope of delivery) • stackable • suitable for float valve 220P (41 l/min at 3 bar) and XtraFlo (250 l/min at 3 bar) • float valve not included in the supplied package!







| ref. no. | description                        | content | l x w x h         |         |     | €   |
|----------|------------------------------------|---------|-------------------|---------|-----|-----|
| 223623   | Water trough                       | 550 l   | 150 x 115 x 58 cm | 1       | 7   | ~ B |
| 223624   | Water trough                       | 1000 l  | 235 x 125 x 58 cm | 1       | 7   |     |
| 223440   | Float valve XtraFlo Top Entry      | -       | -                 | 1/10/20 | 240 |     |
| 223441   | Float valve 220P                   | -       | -                 | 1       | -   | _   |
| 16601    | Outlet for footbath / water trough | -       | -                 | 1/100   | -   | _   |
| 223629   | Ground anchor                      | -       |                   | 1/10    | -   |     |

# **Double Float Drinking Bowl S60**

### for pasture attachments

• drinking bowl made from high-quality plastic • volume: 58 l • for up to 40 large cows • suitable for high and low pressure • incl. complete mounting accessories for barrel attachment • with inner lip to avoid water waste • with 3/4" connection • water connection from above, below or behind • water flow rate: 54 l/min at 5 bar, 41 l/min at 3 bar, 24 l/min at 1 bar • with 2 outlet plugs for easy cleaning • larger outlet (art. 16601) can be retrofitted • valve on the top for rapid access to the valve • weight: 15 kg





| ref. no. | description                        | l x w x h       |       |   | €           |
|----------|------------------------------------|-----------------|-------|---|-------------|
| 223619   | Double Float Drinking Bowl S60     | 90 x 45 x 35 cm | 1     | 8 |             |
| 223441   | Float valve 220P                   | -               | 1     | - |             |
| 16601    | Outlet for footbath / water trough | -               | 1/100 | - | <del></del> |

# **Double Float Drinking Bowl S60**

### for wall and tube mounting

• drinking bowl made from high-quality plastic • volume: 58 l • for up to 40 large cows • suitable for high and low pressure • with inner lip to avoid water waste • with 3/4" connection • water connection from above, below or behind • water flow rate: 54 l/min at 5 bar, 41 l/min at 3 bar, 24 l/min at 1 bar • with 2 outlet plugs for easy cleaning • larger outlet (art. 16601) can be retrofitted • valve on the top for rapid access to the valve • weight: 15 kg





| ref. no. | description                        | l x w x h       |       |   | € |
|----------|------------------------------------|-----------------|-------|---|---|
| 223618   | Double Float Drinking Bowl S60     | 90 x 45 x 35 cm | 1     | 8 |   |
| 223441   | Float valve 220P                   | -               | 1     | - |   |
| 16601    | Outlet for footbath / water trough | -               | 1/100 | - |   |



# **Stainless Steel Water Trough**

• robust trough for wall or floor mounting • available in two sizes (100 cm/50 litres and 190 cm/95 litres) • large drain and inclined trough base ensure rapid draining of the water and self-cleaning of the trough • expansion sealing plugs for quick opening and closing of the drain • drain connection suitable for KG pipe DN 100 • high-efficiency float valve 3/4": 54 l/min at 5 bar, 41 l/min at 3 bar (can be connected on either side) • easy to open valve cover • frost-free down to -15 °C: integrated electric heating 200 W (ref. no. 221142, 221143, 221152, 221153) or can be retrofitted (ref. no. 221094), operation with transformer (not included in the scope of delivery!) • valve XtraFlo with 250 l/min at 3 bar optionally available



|                              | with wall bracket | with floor stand  |  |
|------------------------------|-------------------|-------------------|--|
| Water Trough 100 cm (inside) | 117 x 60 x 64 cm  | 122 x 58 x 102 cm |  |
| Water Trough 190 cm (inside) | 207 x 60 x 64 cm  | 212 x 58 x 102 cm |  |

| ref. no. | description   | length |         | €   |              |
|----------|---|--------|---------|-----|--------------|
| 221140   | Stainless Steel Water Trough with Floor Rack            | 100 cm | 1       |     |              |
| 221141   | Stainless Steel Water Trough with Wall Bracket          | 100 cm | 1       |     |              |
| 221150   | Stainless Steel Water Trough with Floor Rack            | 190 cm | 1       |     |              |
| 221151   | Stainless Steel Water Trough with Wall Bracket          | 190 cm | 1       |     |              |
| 221142   | Heatable Stainless Steel Water Trough with Floor Rack   | 100 cm | 1       |     |              |
| 221143   | Heatable Stainless Steel Water Trough with Wall Bracket | 100 cm | 1       |     |              |
| 221152   | Heatable Stainless Steel Water Trough with Floor Rack   | 190 cm | 1       |     | secure       |
| 221153   | Heatable Stainless Steel Water Trough with Wall Bracket | 190 cm | 1       |     | U-shap       |
| 221145   | Floor Rack for Stainless Steel Water Trough             | -      | 1       | saf | ety mounting |
| 221146   | Wall Bracket for Stainless Steel Water Trough           | -      | 1       |     | ,            |
| 223441   | Float valve 220P  | -      | 1       |     |              |
| 223440   | Float valve XtraFlo Top Entry                           | -      | 1/10/20 | _   |              |
| 221094   | Additional / replacement 200 W Heater                   | -      | 1       |     |              |
| 221144   | Sealing Plugs for Stainless Steel Water Troughs         | -      | 1/20/80 |     |              |



### **AniScale Animal Scale**

This animal scale with cradle stand is ideal for weighing large animals. The animals can easily be put into the cage and held for the weighing procedure. The animal scale can be integrated into trap systems or races.

The scale stand

- weighing platform with rubber mat animals are safe, noise-dampening
- extra robust design hot-dip galvanised with 2 sliding doors, in front and behind incl. 2 panels each 240 cm easy to integrate in palisade trap systems or races

The weighing set

• robust scale beams are mounted below the cage • handles on the scale beams for easy carrying and placement • display with handy carry handle • with LED display • with battery, operating time per charge approx. 30 hours • includes charger • stand for display optionally available

### Functions:

 $\bullet$  stabilisation function, determines the weight of moving animals  $\bullet$  tare function  $\bullet$  sum possible

The complete set consists of stand and scale set.

To combine the animal scale with a trap system, please use the connector frame so as not to distort the weighing result.



| ref. no. | description   |   |    | € |  |
|----------|---|---|----|---|--|
| 291320   | AniScale Animal Scale Complete Set                            |   | 1  |   |  |
| ref. no. | description   |   |    | € |  |
| 291324   | Weighing platform with scale set (no panels or sliding doors) | 1 | -  |   |  |
| 291325   | Scale stand (weighing platform, 2 panels, 2 sliding doors)    | 1 | 2  |   |  |
| 291321   | Weighing platform alone                                       | 1 | -  |   |  |
| 291322   | Scale set (scale beams with display)                          | 1 | -  |   |  |
| 442620   | Sliding door, single  | 1 | -  |   |  |
| 442591   | Fence component without gate                                  | 1 | 18 |   |  |
| 442621   | Connector frame for panels                                    | 1 | -  |   |  |
| 291323   | Stand for display for scale set                               | 1 | -  |   |  |

### **Collar Number Duo**

• effortless attachment and removal thanks to two-part design • optimised recognisability thanks to handy colour code, double-sided labelling and large format (54 x 59 mm) • suitable for neck marking straps up to 40 mm wide




### Major work relief

The Collar Numbers Duo are a huge help, especially if there are livestock changes. Conventional even be fitted without removing the collar.

The special colour coding (one colour for each number) and large format make animal recognition much easier, especially at long distances, with partially concealed digits or in poor lighting conditions. Thanks to the double-sided labelling and colour coding, even twisted collars are no longer a problem.









collar numbers must be pushed from the collar which, due to dirt and soiling, is no longer possible or extremely difficult after even just a short period of use. In some circumstances, complete dismantling of the collar, including equipment such as transponders, sensors or weights, is required even though only one number needs to be changed. By contrast, the Collar Numbers Duo can be opened, removed and inserted in the required position easily. With tethered animals, they can be

### Optimum recognisability







# **Accessories Collar Number Duo**

description

Number 0 (6 pack)

Number 1 (6 pack)

Number 2 (6 pack)

Number 3 (6 pack)

Number 4 (6 pack)

Number 5 (6 pack)

Number 6 (6 pack)

Number 7 (6 pack)

Number 8 (6 pack)

Number 9 (6 pack)

ref. no.

209420

209421

209422

209423

209424

209425

209426

209427

209428

209429

Spare Pins: • 12 pack • plastic

Mounting Tool: • for easier insertion and removal of the pin



colour

black

yellow

orange

red

violet

blue

green

grey

brown

white









# **Numbering Block Large**

• 1-digit • for threading in • large format (50 x 59 mm) • suitable for neck marking straps up to 40 mm wide • set of 10




| ref. no. | description  | ₩  |      | € |
|----------|--------------|----|------|---|
| 208450   | Number 0     | 10 | 1/10 |   |
| 208451   | Number 1     | 10 | 1/10 |   |
| 208452   | Number 2     | 10 | 1/10 |   |
| 208453   | Number 3     | 10 | 1/10 |   |
| 208454   | Number 4     | 10 | 1/10 |   |
| 208455   | Number 5     | 10 | 1/10 |   |
| 208456   | Number 6 + 9 | 10 | 1/10 |   |
| 208457   | Number 7     | 10 | 1/10 |   |
| 208458   | Number 8     | 10 | 1/10 |   |



# **Marking Collar**

- with sturdy plastic clamp fastenerbelt width 40 mm





| ref. no. | length | colour        |          | € |
|----------|--------|---------------|----------|---|
| 20923    | 130 cm | green / white | 1/10/100 |   |
| 20925    | 130 cm | blue          | 1/10/100 |   |
| 20921    | 130 cm | white / black | 1/10/100 |   |
| 20924    | 90 cm  | green / white | 1/10/100 |   |
| 20926    | 90 cm  | blue          | 1/10/100 |   |



# **Rain Gauge with Counter**

• plastic • easy installation on a round pile up to Ø 27 mm • precipitation is easy to read: 1 scale bar = 1 mm = 1L / m2 • monthly rainfall is easy to total up using the adjustable counter. Simply turn the rotary ring by the respective additional rainfall amount







# **5in1 Multi-function Oil Spray**

Rust solvent, lubricant, contact spray, corrosion protection and metal care agent

Rust solvent, lubricant, contact spray, corrosion protection and metal care agent Universally applicable in agriculture and forestry, the workshop, industry and household.

- very good lubrication properties, even at high pressures displaces moisture to a large extent and provides good corrosion prevention releases locked, rusted and jammed mechanical systems, bolts and vehicle and machine parts very good creep properties penetrates into the smallest of gaps and cracks
- $\bullet$  cares for metals with a thin protective film  $\bullet$  temperature resistant from -10 °C to +150 °C  $\bullet$  silicone and resin free



universally applicable in many areas

# **All-purpose Shovel**

• versatile, e.g. as a snow or grain shovel • patented reinforced blade edge • 3-part handle • glass reinforced handle • handle is robustly inserted and screwed together • with D-handle

Plug-in system for two lengths!





29698

| ref. no. | description               | width | height |   |     | € |
|----------|---------------------------|-------|--------|---|-----|---|
| 29697    | Shovel, large, no welts   | 44 cm | 40 cm  | 1 | 80  |   |
| 29698    | Shovel, small, with welts | 29 cm | 36 cm  | 1 | 100 |   |

29697

### **Grain Moisture Meter TwistGrain**

- unique electric 3-point measurement of moisture with test pressing
- TwistGrain is programmed for many crops: wheat, rye, barley, triticale, oats, rapeseed, maize etc.
- the audio signal in the screw cap confirms if the test sample has been pressed sufficiently hard
- precise measurement of whole grains of many plant types
- the measurement result can be read in bright sunlight as well as the dark thanks to the graphic display with backlight and high contrast, as well as a wide viewing angle
- glass-fibre reinforced screw cap and housing made from shakeproof material (ABS) ensure your device is extremely strong
- fast and easy to use ideal for working in the field
- you can measure grain moisture in seconds with a very small device that weighs just 0.5 kg
- dimensions: 16.5 x 7 x 7.5 cm
- 2-year guarantee

### The set includes:

- DRAMINSKI Twist Grain moisture meter with cap
- carrying pouch
- carrying strap for the pouch to hang up the device
- incl. 4 alkali-manganese batteries, type AA, 1.5 V
- incl. 1 battery, type CR2032, 3 V (in the cap)
- includes operating instructions











### **Grain-Moisture Level Reader GrainMaster GMSV2**

### with grinder

The grain is ground and pressed using special grinding plated integrated into the measuring cell, which ensures a high level of reliability and reproducibility of the obtained results

- GrainMaster is programmed for the following crops: wheat, rye, barley, triticale, oats, rapeseed, maize. Other cereals can be retrofitted.
- USB interface for software and calibration update
- graphic LCD display (2") LED backlit display
- sample volume: 10 ml

### Accuracy:

- $\pm$  1.0 % in the range of up to 10 % moisture content
- $\pm$  1.2 % in the range of over 10 % moisture content

| technical data                     |  |
|------------------------------------|--|
| Weight:                            | 1550 g   |
| Dimensions:                        | 21 x 11 x 11 cm                                      |
| Filling the measurement container: | manual, using the measurement beaker                 |
| Power supply:                      | 9 volt battery, discharge is automatically indicated |
| Display:                           | LCD display, alphanumeric, 2 x 16 digits             |
| Resolution:                        | 0.1 % moisture content                               |
| Memory:                            | Flash card   |
| Temperature compensation:          | Automatic  |
| Measuring temperature:             | +10 to +35 °C  |
| Storage temperature:               | +10 to +45 °C  |







# **Control for LED Lighting**

This lighting control allows you to switch the artificial stable lighting on or off, on a timer and regardless of existing daylight, or even achieve a constant light level (e.g. min. 200 lux) through automatic dimming. This means it ensures ideal lighting conditions throughout the day and year while minimising electricity consumption. Comfort for animals and humans!

• controls lighting dependent on time and/or daylight • four different lighting circuits (groups) can be independently controlled, two of which with a dimming function • suitable for LED lights with 1...10V interface • standard surface-mount housing for mounting in the equipment room • dust and moisture protection (IP54) • maximum switching power of 11kW • suitable e.g. for up to 50 150 watt lights (up to 15 lights on the dimmable circuits 1 and 2, and up to 10 lights on circuits 3 and 4) • supplied with a light sensor (can request up to four light sensors) • input for up to four button signals • easy to use with display and three buttons • easy to install by your electric company • with extensive documentation and terminal description

| technical data                    |             |
|-----------------------------------|-------------|
| supply voltage:                   | 230 / 400 V |
| fusing:                           | 3-pin B16A  |
| max. current value per output:    | 16 A        |
| max. total power circuit 3 and 4: | 16 A        |
| number of circuits:               | 4           |
| number of dimmable circuits:      | 2           |
| max. switching capacity:          | 11 kW       |
| dimming function circuit 1 and 2: | 110 V       |
| max. number of light sensors:     | 4           |
| max. number of button signals:    | 4           |
| Protection type:                  | IP54        |

| ref. no. | description              |   | € |
|----------|--------------------------|---|---|
| 345000   | Control for LED lighting | 1 |   |
| 345001   | Sensor for control       | 1 |   |



# **LED Oval Light**

- ideal for passage areas, garage, basement, etc.
- · suitable for outdoor use
- · sturdy plastic housing with glazed cover
- splash-proof
- · ceiling or wall mounting
- with energy-efficient, SMD LED chips
- up to 80 % less power consumption
- cannot be dimmed

technical data Output:

Luminous efficacy:

Input voltage:

Protection type: Dimensions (L x W x H):

Chip service life (L70):

Colour temperature:

Colour rendering (CRI):

Light flux:

Angle:







| ref. no. | A       | € |
|----------|---------|---|
| 2/15606  | 1/10/30 |   |
|          |         |   |

The outdoor spotlights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

# **LED Floodlight**

 $\bullet$  robust housing made from cast aluminium with safety glass  $\bullet$  robust tubular frame with cable bracket • with adjustable clamping bracket • with plastic carrying handle • 230 volt connecting cable with earthed plug, length 3 m • with energy-efficient, SMD LED chips • up to 80 % less power consumption • suitable for outdoor use • cannot be dimmed • GS approved

6.500 K

Ra > 80 IP 54

16.9 x 11.5 x 7.6 cm





2 years warranty

| technical data                     |                         |
|------------------------------------|-------------------------|
| Output:                            | 50 W                    |
| Light flux:                        | 3,750 lumen             |
| Luminous efficacy:                 | 75 lm/W                 |
| Angle:                             | 100°                    |
| Chip service life (L70):           | > 35.000 h              |
| Input voltage:                     | 220 - 240 V / 50 Hz     |
| Colour temperature:                | 6.000 K                 |
| Colour rendering (CRI):            | Ra > 80                 |
| Protection type:                   | IP 65                   |
| Dimensions with frame (L x W x H): | approx. 32 x 22 x 40 cm |

The outdoor spotlights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

| ref. no. |     | € |
|----------|-----|---|
| 345604   | 1/2 |   |



## Mobile LED Battery Spotlight WorkFire Pro

• sturdy plastic housing with silicon edge protection • splash-proof and shock-resistant • adjustable stand, can also be used as a carrying handle or mounting bracket • with On/Off switch • 3 light levels: 100 % - 50 % - 20 % • li-ion battery with a charge status display and integrated overcharging and deep discharging protection • confusion-proof low-heat device charging cable with earthed plug • with energy-efficient, SMD LED chips • up to 80 % less power consumption • suitable for outdoor use

| technical data           |                                       |
|--------------------------|---------------------------------------|
| Output:                  | 20 W                                  |
| Light flux:              | 1,600 lumen                           |
| Luminous efficacy:       | 80 lm/W                               |
| Battery type:            | Lithium-ion                           |
| Battery nominal voltage: | 7,4 V                                 |
| Battery capacity:        | 4400 mAh                              |
| Charging time:           | 5 h                                   |
| Hours of light:          | 2.5h (100 %), 5h (50 %),<br>8h (20 %) |
| Angle:                   | 100°                                  |
| Chip service life (L70): | > 35.000 h                            |
| Input voltage:           | 220 - 240 V / 50 Hz                   |
| Colour temperature:      | 6.000 K                               |
| Colour rendering (CRI):  | Ra > 80                               |
| Protection type:         | IP54                                  |
| Dimensions (L x W x H):  | approx. 23 x 16 x 6 cm                |



The outdoor spotlights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

| ref. no. |     | € |
|----------|-----|---|
| 345605   | 1/6 |   |



## **LED Work Light WorkFire**


- powerful 3 watt COB LED 3 additional LEDs in the luminaire head enable economical torch operation fold-out hook that can be turned 360° magnet on the back sturdy and handy ABS plastic housing non-slip rubber coating in the handle area splash-proof 200 lumen
- batteries included (3 x type AA) dimensions (L x B x H): approx. 20 x 6.2 x 3.4 cm only available in display











MQ

### **LED Torch MiniFire**

- $\bullet \ compact \ and \ sturdy \ housing \ made \ from \ aluminium \ \bullet \ splash-proof \ \bullet \ non-slip \ ribbing \ in \ the \ handle \ area$
- 5 light functions: 100 % 50 % 10 % flashing SOS focus function with wrist loop red light ring 3 watt high-performance LED from CREE batteries included (3x type AAA) 120 lumen
- length approx 12.3 cm

ref. no.



# **LED Torch ProFire**

- solid and sturdy housing made from aluminium splash-proof non-slip ribbing in the handle area • 2 light levels: 100 % - 50 % • focus function • with wrist loop • 6 watt high-performance LED from
- CREE 500 lumen batteries included (3 x type C) length approx. 21 cm

| ref. no. |         | € |
|----------|---------|---|
| 345602   | 1/12/24 |   |



## **Box Trap Alive Predator Self-Assembly Kit**

• works well both outdoors and indoors • galvanised wire mesh and aluminium parts guarantee long durability • live traps must be darkened to avoid unnecessary stress, as per the valid statutory provisions



Stable assembly kit mounted with just a few actions!

| ref. no. | description                          |   | € |
|----------|--------------------------------------|---|---|
| 299486   | for cats, martens, rabbits, polecats | 1 |   |
| 299488   | for foxes, badgers                   | 1 |   |
| 299487   | for young foxes, martens             | 1 |   |

## **Vole Trap VoleStop**

• easy-to-use vole trap with a unique design • extremely reliable and excellent impact force for successful capture • just a few actions are needed and the trap is armed in seconds • the size of the trap is designed so that a hole of just a few centimetres is all that's needed • the accessory set (can be ordered separately), comprising a search rod and hole digger, makes the work easier • the trap is easy to spot from outside thanks to the cat head design • The trap is set by pulling out the red collar — as long as this is visible, the trap has not yet been triggered! The trap has been triggered when only the cat head is visible without a red collar. • field mice and voles are captured from both directions • eco-friendly, reusable and if used correctly harmless to users and household pets • accessory set comprising search rod and hole digger



| ref. no. | description        |      | € |
|----------|--------------------|------|---|
| 299821   | Vole Trap VoleStop | 1/10 |   |
| 299836   | Accessory set      | 1/4  |   |



### **Vole-free Power Bar**

- 8 individually packed bars in 10 g portions innovative bait bar for vole control attractive bait with efficient active substance and 68% less chemistry
- $\bullet$  reliably protects vegetables, fruit and ornamental plants  $\bullet$  no contact with bait since it is in the form of a ready to use bar







## cit Mite-ExSil Mite Powder Spray\*

The latest development in the war against poultry red mite and other parasites in stables!

- simple application silicon dioxide attacks the wax layer on mites, causing them to dessicate and die
- aerosol spray allows the active ingredient to be applied accurately and especially in all corners and
  cracks spray jet leaves behind a white layer of powder on sprayed areas. This means it is easy to check
  when and where applications need to be repeated especially effective at combating poultry red mite,
  other types of poultry mite, fleas and ticks



| ref. no. | content |      | € |
|----------|---------|------|---|
| 15448    | 500 ml  | 1/12 |   |

Amorphous silicone dioxide
Pyrethrin + pyrethroids

# DiaCarid \*

#### combats red fowl mites and crawling insects

• an effective pesticide to combat red fowl mites and crawling insects • effectively repels crawling bugs such as mites, ants, silverfish and woodlice • a fine powder made of fossilised plankton is also effective in damp air • the mites' protective wax film is destroyed on direct contact with DiaCarid. The pests are therefore instantly demobilised and dry out • the special structure makes it impossible to build up resistance • spread DiaCarid in the places where mites and other crawling insects hide • amount to use 4 g/m² (enclosure)



#### BioAcarid

| ref. no. | content |      | € | active agent |
|----------|---------|------|---|--------------|
| 299799   | 100 g   | 1/12 |   | Kieselguhr   |

Suitable for organic farms! treats an area of 25  $\,\mathrm{m}^2$ 

# **Lenticular Slug Power Packs**

• 100% bait output due to patented lenticular shape with 50% reduction in active substance compared to conventional slug pellets • irresistible slug luring action • rain and mould resistant due to protective lenticular formula • harmless to domestic and working animals and to the environment • absolutely dust-free • rate of application: 0.6 g/m² (approx. 40 screw lenses per m²)



#### active agent

30g/kg metaldehyde

| ref. no. | description        |      | € |
|----------|--------------------|------|---|
| 299891   | 275 g - shaker can | 1/20 |   |
| 299892   | 4 x 200 g - pack   | 1/20 |   |
| 299865   | 2 x 100 g          | 1/20 |   |

Pflanzenschutzzone

| ref. no. | description                                |       |  |
|----------|--|-------|--|
| 299873   | 162 x 275 g, Special Offer Display         | 1/162 |  |
| 299893   | 60 x (4 x 200 g), Special Offer Display    | 1/60  |  |
| 299866   | 162 x (2 x 100 g), . Special Offer Display | 1     |  |

\* Take care when using biocides. Always read the label and product information before use!

**NEW** 



### **Cordless Tooth Grinder Premium**


• battery-operated tooth grinder for fast and painless grinding of newborn piglets' teeth • Li-ion battery (12 V / 2 Ah) • one battery charge provides enough grinding for 8-10 litters • battery operation provides greater flexibility with regard to the place of use • short charge time thanks to 1h charger • grinding stone with double diamond dust layer, ensuring long service life • lightweight, ergonomic shape and soft grip guarantee fatigue-free working • rubber bearings provide protection against penetrating moisture • motor brake – accessory stops immediately after switching off the tool • integrated spindle lock – no accidental starting up of the collet lock when tool is in operation • with continuous speed regulator (5,000 - 33,000 r/min) incl. grinding tool, battery and aluminium protective cap • supplied in a handy carrying case



| ref. no. | description   |          | € |
|----------|---|----------|---|
| 226680   | Cordless Tooth Grinder Premium                      | 1        |   |
| 226681   | Spare battery                                       | 1        |   |
| 226682   | Spare charger                                       | 1        |   |
| 226610   | Aluminium cap                                       | 1        |   |
| 22914    | Grinding body ø 7mm                                 | 1/10/200 |   |
| 226660   | Replacement battery for predecessor item no. 226650 | 1        |   |
| 226670   | Replacement charger for predecessor item no. 226650 | 1        |   |

## **Play Rope**

• made from organic natural materials (100 % cotton) • woven • on a coil



## **Seche-etable Stable Drying Agent**


• highly effective bedding drying agent for dryness and hygiene in stables • usable with pigs, cattle, horses and poultry • excellent drying of lying areas thanks to the good liquid binding properties of the materials it contains • reduces illness incidence and improves air quality thanks to the disinfectants and essential oils it contains • especially for use in farrowing stables (piglet nest bedding and powdering the newborn piglets) • how to use: 30 - 300 g/m2 depending on soiling and illness incidence

| ref. no. |   |    | € |
|----------|---|----|---|
| 29346    | 1 | 50 |   |

## **Powder Disperser**

- specially developed for hygienic litter powder like Seche-etable stable drying agent or lime
- suitable for all common screwdrivers (min. 600 rpm, 13 mm chuck)
- the bedding material is evenly distributed in the stalls, saving you a lot of bedding products
- adjustable dispenser opening for precise dosage of lime/powder
- highly productive: 120 boxes of 100 g powder each with one filling

| technical data      |           |
|---------------------|-----------|
| Contents:           | 12 litres |
| Filled weight:      | 8 - 10 kg |
| Empty weight:       | 3 kg      |
| Material container: | LDPE      |





# **Nylon Dosing Syringe with Input Cannula**


- unbreakable and handy syringe syringe volume: 50 ml with threaded connection
- incl. curved input cannula

| ref. no. | description                | content | SB |       | € |
|----------|----------------------------|---------|----|-------|---|
| 23500    | Nylon syringe with cannula | 50 ml   | -  | 1/150 |   |
| 23500-1  | Input cannula, single      | -       | -  | 1/300 |   |

# **TU Flex-Master Dosing Syringe**

 $\bullet$  robust plastic syringe made of TPX  $\bullet$  replaceable Luer-lock made of stainless steel  $\bullet$  can be boiled for disinfection  $\bullet$  in SB-pack  $\bullet$  incl. spare sealing ring

| ref. no. |           | content |          | € |
|----------|-----------|---------|----------|---|
| 23710    | Luer-lock | 10 ml   | 1/20/120 |   |
| 23711    | Luer-lock | 20 ml   | 1/20/120 |   |
| 23712    | Luer-lock | 30 ml   | 1/20/120 |   |
| 23713    | Luer-lock | 50 ml   | 1/20/120 |   |
| 23720    | Thread    | 10 ml   | 1/20/120 |   |
| 23721    | Thread    | 20 ml   | 1/20/120 |   |
| 23722    | Thread    | 30 ml   | 1/20/120 |   |
| 23723    | Thread    | 50 ml   | 1/20/120 |   |



## **Plastic Drinker with Feet**

• for poultry in furnished cages • with carry handle and proven bayonet closure • incl. feet, thus less soiling • food safe



| ref. no. | content | MQ |      | $\blacksquare$ | € |
|----------|---------|----|------|----------------|---|
| 70121    | 1,5 l   | 1  | 1/10 | 720            |   |
| 70122    | 3,0     | 1  | 1/10 | 520            |   |
| 70123    | 5,0 l   | 1  | 1/10 | 300            |   |
| 70124    | 8,0 l   | 1  | 1/10 | 200            |   |
| 70125    | 10.0 l  | 1  | 1/10 | 200            |   |



## **Automatic Feeder with Feet**

 $\bullet$  for poultry in furnished cages  $\bullet$  incl. feet, thus less soiling  $\bullet$  also suitable for hanging  $\bullet$  food safe



| ref. no. | content | MQ |      |     | € |
|----------|---------|----|------|-----|---|
| 70126    | 2,4     | 1  | 1/10 | 600 |   |
| 70127    | 4,8 l   | 1  | 1/10 | 240 |   |
| 70128    | 9,6     | 1  | 1/10 | 140 |   |
| 70129    | 14,4 l  | 1  | 1/5  | 40  |   |





### **Automatic Chicken Door**

The automatic chicken door allows the flaps, doors or sliders in poultry stalls to be automatically opened and closed.

The automatic chicken door has various functions for opening and closing the slider:

- daylight-dependent control with light sensor
- time-dependent control, can differentiate between weekdays and weekends
- manual control, on the unit or via connected switch

The automatic chicken door is fitted with safety features. A time delay on the light signal prevents unwanted opening during lightning. If the slider encounters resistance by an animal when closing, the process is stopped and then repeated.

Included in scope of delivery: control with integrated motor and cable, AC adapter, batteries, light sensor, pulley set, instruction manual





| ref. no. | description               | €    |  |
|----------|---------------------------|------|--|
| 70550    | Automatic Chicken Door    | 1/10 |  |
| 70551    | Pulleys, 4-pack           | 1    |  |
| 70560    | Sliding door 220 x 330 mm | 1/20 |  |
| 70570    | Sliding door 300 x 400 mm | 1/20 |  |





## **Chicken Coop Bonny**

#### with Metal Frame on Ground

• made from high quality China-fir • with sliding window for variable air circulation • metal frame on ground protects against moisture and the deterioration of the wood • increased safety due to an additional lock per door • access between the outdoor pen and the resting place can be blocked off • resting place dimensions: 67 x 56 cm • incl. 2 laying nests and 2 perches • durable design • 5 cm high retractable plastic basin, makes cleaning easier • glazed with protective wood colour • weather-proofed bitumen roof • comes disassembled in cardboard box • easy assembly, incl. assembly instructions















ref. no. 81713 1 x w x h 181 x 65 x 118 cm MQ 1

5



### **Rabbit Hutch XXL Vario**

- with integrated, closable hay rack
- 6 cm high retractable plastic basin, makes cleaning easier
- with high-quality grille
- 2 front doors that can be opened separately
- increased safety due to a second lock per door
- with side door for free outlet
- tunnel to resting area
- with additional storage space
- weatherproof, plastic fold-up roof with stay mechanism on main roof
- height-adjustable plastic feet
- glazed with protective wood colour
- internal height: 60 cm
- comes disassembled in cardboard box
- incl. assembly instructions, easy assembly

















| ref. no. | lxwxh            | MQ |   | € |
|----------|------------------|----|---|---|
| 81709    | 155 x 76 x 80 cm | 1  | 5 |   |

### **Rodent House Browni**

#### with Metal Frame on Ground

- made from high quality China-fir floors can be blocked off from each other
- high pull-out plastic tray makes cleaning easier metal frame on ground protects against moisture and the deterioration of the wood glazed with protective wood colour internal height: 50 cm per floor with high-quality grille
- folding bitumen roof with stay mechanism 3 doors that can be opened separately• tunnel to resting area comes disassembled in cardboard box
- incl. assembly instructions, easy assembly thanks to slot-in system













| ret. i | no. |
|--------|-----|
| 817    | 10  |

1x w x h 115 x 64 x 108 cm



## Open-air Enclosure with Breakout Barrier

- zinc-plated design incl. sun protection
- perch with 2 doors bar spacing is 3 cm
- easy to assembly with ground spikes



| ref. no. | lxwxh            |
|----------|------------------|
| 81712    | 180 x 90 x 75 cm |





€

ref. no. 81714 description
Replacement Sun Screen for 81712

MQ 1

# **Extension Unit with Escape Lock**

- can be added on to the side of 82825
- zinc-plated design
- · with additional door
- · with connecting rod for added stability

lxwxh

230 x 76 x 70 cm

• bar spacing is 3 cm

ref. no.

81711



Check the distance between the bars for each animal before use.

MQ

1



### Ear Muff for Children

- specially developed for children aged 5 12
- unique headband design ensures low contact pressure
- · especially light
- continuously adjustable, padded headband
- generous space underneath the earmuffs minimises build-up of heat
- uses: everyday situations such as studying in loud environments, but also noisy leisure activities such as music and sport events, accompanying parents doing DIY etc.
- insulation value SNR = 25 dB
- complies with EN 352-1



### Half-Mask Set ETNA

#### incl. filter pair A1P2

ref. no. 34493

- can be used up to 30 x the MAK value
- central exhalation valve made from silicone works even in extreme temperatures
- computer-aided design, made to fit all face sizes
- made from TPE rubber and PP
- protects against stripper, herbicide, paint and solvent vapours

1/6/24

• extra-lightweight system with optimal weight distribution thanks to four elastic bands

• dual filter system for reduced exhalation resistance

- filter can be quickly changed with bayonet fastener
- unrestricted field of vision compatible with safety goggles
- 2 filters A1P2 R included in the scope of delivery
- appealing blister packaging



| ref. no. | SB |     | € |
|----------|----|-----|---|
| 34535    | 1  | 1/9 |   |

## Replacement Filter Pair for Respiratory Mask

- · attractive blister packaging
- can be used with the ETNA 34535 half-mask
- combination of active carbon filter and particle filter
- the ideal partner for paint spraying, application and varnishing, but also for mechanical sanding
- comply with European standards 6055: EN 14387:2004 + A1:2008 A2EN140 and 5925: EN 143:2000 P2 R

| Designation        | area of use           | Fabrics                       |
|--------------------|-----------------------|-------------------------------|
| Filter Set A1P2    | <5000 ppm (0,5 vol %) | Painting, pesticides          |
| Filter Set ABEK1P3 | <1000 ppm (0,1 vol %) | Manure, ammonia, acidic gases |

| ref. no. | description        | SB |      | € |
|----------|--------------------|----|------|---|
| 34536    | Filter Set A1P2    | 2  | 1/16 |   |
| 34537    | Filter Set ABEK1P3 | 2  | 1/16 |   |



### **Mechanic Glove Helios**

#### The Lightweight One

Extremely good fit and low weight for optimal comfort. The glove for precision work.

• 0.5 mm ultra-thin but still durable synthetic material for precision work • fully encompassed with Lycra for complete freedom of movement and comfort — the glove feels like a second skin • honeycomb silicone matrix on the fingers and palms for optimal grip • exposed points on the back of the hand reinforced with silicone • conductive finger tips so you can still use touch screens

| Evaluation              |      |
|-------------------------|------|
| Durability              | ••   |
| Dexterity               | •••• |
| Moisture protection     |      |
| Resistant to grease/oil |      |
| Slip-resistance         | •••• |
| Breathability           | •••• |



### **Mechanic Glove Horen**

### The Grippy One

Extraordinary grip, perfect fit, breathable – nothing grips better than this glove!

• specially formed silicone matrix (anti-slip coating) on fingers and palms for optimal grip and easy working • stretch material on the back and cuffs ensure perfect fit • breathable 4-way stretch between the fingers for additional temperature regulation • tab makes it easier to put the gloves on • terry cloth sweat zone for more comfort

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••  |
| Dexterity               | •••• |
| Moisture protection     | ••   |
| Resistant to grease/oil | •    |
| Slip-resistance         | •••• |
| Breathability           | •••• |





### **Mechanic Glove Wotan**

#### The Anti-shock Glove

Extraordinary grip, perfect fit — for professionals. Protects your hands from shocks and impact injuries.

• snug fit for precision work • silicone print on fingertips and palms for optimal grip • padded on the inside palm to cushion vibrations • ingenious padded pattern for more freedom of movement • elastic Spandex back for perfect fit and breathability • Velcro to prevent debris entering in and for perfect fit • knuckle protection made of neoprene

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••• |
| Dexterity               | •••  |
| Moisture protection     | ••   |
| Resistant to grease/oil | •    |
| Slip-resistance         | •••• |
| Breathability           | •••• |



### **Mechanic Glove Hermes**

#### The Abrasion-resistant One

Comfort meets robustness. Comfortable and secure all-round protection for the entire hand thanks to large-scale abrasion protection.

• vibration cushioning on the palms for fatigue-free work • double-reinforced PVC textured palms and fingers for excellent durability and grip, also suitable for working with ropes • reinforced thumb-index finger area for longer life • elastic Spandex back for perfect fit and breathability • Velcro to prevent debris entering in and for perfect fit • knuckle protection made of neoprene • terry cloth sweat zone for more comfort • tab makes it easier to put the gloves on

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••• |
| Dexterity               | •••• |
| Moisture protection     | ••   |
| Resistant to grease/oil | •    |
| Slip-resistance         | •••  |
| Breathability           | •••• |



### **Mechanic Glove Zelos**

#### The All-rounder

Snug fit, elastic back, good design – your go-to glove for everyday work

• elastic Spandex means a breathable back and good fit • palms made from 1 mm thick, soft, washable microfibre • Velcro to prevent debris entering in and for perfect fit

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••  |
| Dexterity               | •••• |
| Moisture protection     | •    |
| Resistant to grease/oil |      |
| Slip-resistance         | •••  |
| Breathability           | •••• |



## **Mechanic Glove Ajax**

### The Stylish One

Secure, balanced, abrasion-free, complete all-round protection — the best glove in the series

• TPR protectors on the back to absorb shocks and to protect tissues from tearing • grooved and reinforced areas on the palm for longer life, especially when working with ropes • vibration absorbers on the base of the thumb to absorb shocks • palms made from 1 mm thick, soft, washable microfibre • Velcro to prevent debris entering in and for perfect fit

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••• |
| Dexterity               | •••• |
| Moisture protection     | •••  |
| Resistant to grease/oil | •    |
| Slip-resistance         | •••  |
| Breathability           | •••• |







# **Mechanic Glove Melyc**

#### The Ice-breaker

Warm, soft, waterproof. A work glove optimised for cold weather.

• waterproof breathable membrane for dry hands • fleece insulation keeps your hands comfortably warm • extra-long, slim-fitting, high-quality cuff prevents snow getting in • structured faux leather on the palms for good grip • exposed points on the back of the hand reinforced with silicone

| Evaluation              |      |
|-------------------------|------|
| Durability              | •••  |
| Dexterity               | ••   |
| Moisture protection     | •••• |
| Resistant to grease/oil | •••• |
| Slip-resistance         | •••• |
| Breathability           | •••  |
| Winter                  | •••• |



## **Garden Glove Garden Care**

• seamless fine-knit gloves (13 gauge) made of polyester • perfect fit and easy movement because of uncoated back • breathable • very elastic coated with thin latex foam • attractive colours and nice flower design on the back • size: uni • for gardening

| Evaluation              |       |
|-------------------------|-------|
| Durability              | •••   |
| Dexterity               | ••••  |
| Moisture protection     | •••   |
| Resistant to grease/oil | •     |
| Slip-resistance         | ••••  |
| Breathability           | • • • |



#### with presentation tag

| ref. no. | colour     | MQ |        | € |     |
|----------|------------|----|--------|---|-----|
| 297577   | red        | 1  | 1/6/60 |   | NEW |
| 297276   | yellow     | 6  | 1/6/60 |   | NEW |
| 297278   | purple     | 6  | 1/6/60 |   | NEW |
| 297279   | light-blue | 6  | 1/6/60 |   | NEW |









| Wir bemühen uns laufend unser Programm zu verbessern und auf dem neuesten Stand zu halten. Änderungen in den Ausführungen behalten wir uns deshalb vor. Mit Erscheinen dieses Kataloges verlieren alle alten Kataloge und Preislisten für diese Produkte ihre Gültigkeit. Bei allen angegebenen Preisen handelt es sich um unverbindliche Preisempfehlungen des Herstellers und verstehen sich inklusive gesetzlicher Mehrwertsteuer. Alle Angaben erfolgen vorbehaltlich Satz- und Druckfehler. Preisänderungen und Irrtum vorbehalten. Änderungen in Farbe und Ausführung aus drucktechnischen Gründen möglich! |
|---|
| Nachdruck - auch auszugsweise - darf nur nach vorheriger Genehmigung erfolgen.  © 01/2018   |

PR313=Neuheiten\_Agrar\_2018\_ohnePreis\_EN